

Product Name:	Bluelab pH Pen
Product Code:	PENPH
UPC Code:	9421024920234
Country of Origin:	New Zealand
Tariff Code:	9027.80
Shipping Quantity:	10 kg = 100 units / 25 kg = 230 units
Packaging Information:	
Packaged Weight:	0.144 kg / 0.317 lb
Packaged Length:	205 mm / 8.07 in
Packaged Width:	55 mm / 2.165 in
Packaged Height:	32 mm / 1.26 in

Sales Description:

NOTE: this copy can be used in brochures, catalogues or online

The ultimate handy solution for measuring pH!

Plants get their nutrition from minerals but they can only get all the right minerals they need if certain conditions are right.

A key factor that affects food uptake is whether your solution is acid or alkaline. We measure this in pH.

The Bluelab pH Pen is the latest innovation for hand held meters. It provides a compact quick and handy way to manage the success of your crops to ensure maximum uptake of nutrients. Teamed with our Bluelab EC Pen or Bluelab ppm Pen, you have a handy, convenient and accurate system for ensuring optimum plant growth and health.

Now, isn't that handy?

Features:

- Measures pH and temperature
- Selectable units for °C & °F
- Backlit LCD display
- Double junction probe (not replaceable)
- Successful pH calibration indicator
- Hold reading function
- Low battery indicator
- Fully waterproof
- Auto off function
- Automatic temperature compensation

Product Guarantee:

One year free repair or replacement guarantee.



Product Image:



Product images available for Screen or Web use:

- Bluelab-pHPen-F-MR-flat-RGB.jpg
- Bluelab-pHPen-F-WEB.jpg
- Bluelab-pHPen-F-Web-sml.jpg
- Bluelab-pHPen-C-MR-Flat-RGB.jpg
- Bluelab-pHPen-C-WEB.jpg
- Bluelab-pHPen-C-WEB-sml.jpg

Product images available for PRINT:

Note: these images are high resolution in CMYK.

- Bluelab-pHPen-C-MR-flat-CMYK.tif
- Bluelab-pHPen-F-MR-flat-CMYK.tif

Technical Specifications:

Measurement Range:	0.0 – 14.0 pH 0 – 50°C / 32 – 122°F
Resolution:	0.1 pH 1°C / 1°F
Accuracy at 25C / 77F:	± 0.1 pH, ± 1°C / ± 2°F
Automatic Temperature Compensation:	Yes
Operating Environment:	0 – 50°C / 32 – 122°F
Calibration:	Two point, pH 7.0 & pH 4.0 or pH 10.0
Power Source:	1 x AAA alkaline battery
User Manual Languages Available:	English; Español-España; Español-Latinoamérica; Français; Français-Canada; Nederlands; Deutsch
Certifications:	CE and FCC

{This Product Information Sheet is NOT intended for distribution to end users.}